

RECOMMENDED SWAGING & SKIVING CHART

BRAIDED HOSES

NOMINAL BORE	DN	5	6	8	10	12	16	19	25	31	38	51
INTERNAL DIAMETER	INCHES	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
	MM	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8
B12T..N	05000	05000-03	05000-04	05000-05	05000-06	05000-08	05000-10	05000-12	05000-16	05000-20	05000-24	05000-32
1SN	STANDARD	16.0	18.0	18.6	20.5	23.4	27.0	30.8	39.1	48.5	57.0	69.4
	FITTINGS	n.s.	n.s.	n.s.	n.s.	n.s.	n.s.	n.s.	n.s.	n.s.	n.s.	n.s.
B12T..N	05000	05000-03	05000-04	05000-05	05000-06	05000-08	05000-10	05000-12	05000-16	05000-20	05000-24	05000-32
2SN	STANDARD	16.7	18.5	19.6	21.3	24.4	28.2	32.0	40.3	50.8	59.0	72.7
	FITTINGS	n.s.	n.s.	n.s.	n.s.	n.s.	n.s.	n.s.	n.s.	n.s.	n.s.	n.s.
B1R..	05100	05100-03	05100-04	05100-05	05100-06	05100-08	05100-10	05100-12	05100-16	05100-20	05100-24	05100-32
1ST	STANDARD	15.2	17.2	18.8	21.0	25.4	28.2	32.2	39.8	46.6	53.0	66.2
	FITTINGS	18	21	22	23	25	28	34	37	43	47	62
B2R..	05200	05200-03	05200-04	05200-05	05200-06	05200-08	05200-10	05100-12	05200-16	05200-20	05200-24	05200-32
2ST	STANDARD	17.6	17.8	20.3	23.0	25.7	29.9	33.5	41.2	50.8	57.2	69.5
	FITTINGS	18.5	21	22	23	25	28	34	37	43	47	64