

SPIRAL HOSES

NOMINAL BORE (mm)	DN	5	6	8	10	12	16	19	25	31	38	51
INTERNAL DIAMETER	INCHES	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
	mm	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8

4SP	FERRULE		05404-04V		05404-06V	05404-08V	05404-10V	05404-12V	05404-16V	05404-20V	05404-24V	05404-32V
	FOR STANDARD		19.2		23.2	26.3	29.8	33.5	41.8	54.6	58.5	74.0
	FITTINGS		21 External		23 External	27 External	31 External	36 External	48 External	54 External	62 External	64 External

4SP	FERRULE				05400-06V	05400-08V	05400-10V	05400-12V	05400-16V			
	FOR STANDARD				25.8	28.5	32.9	36.0	43.5			
	FITTINGS				n.s	n.s	n.s	n.s	n.s			

4SH	FERRULE							05400-12V	05400-16V	05400-20V		
	FOR STANDARD							36.0	43.7	54.0		
	FITTINGS							n.s	n.s	n.s		

4SH	FERRULE							05405-12V	05405-16V	05405-20V	05405-24V	05405-32V
	FOR INTERLOCK							33.9	41.5	50.2	57.2	74.2
	FITTINGS							15 Internal	17 Internal	21.5 Internal	22 Internal	29 Internal
								52 External	67 External	74 External	81 External	85 External

4SH	FERRULE									05403-20V	05403-24V	05403-32V
	FOR STANDARD									47.2	58.0	70.5
	FITTINGS									54 External	62 External	64 External

*These dimensions are a guideline only compatible with Vitillo Hose & Fittings

n.s. = No skive



EHRCO Limited

Unit H
Peartree Business Park
Crackley Way
Peartree Lane
Dudley
DY2 0UW

sales@ehrco.ltd.uk

www.ehrco.co.uk

T: 01384 245 000

SPIRAL HOSES

NOMINAL BORE (mm)	INTERNAL DIAMETER	DN	5	6	8	10	12	16	19	25	31	38	51
		INCHES	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
		mm	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8
R13	FERRULE								05405-12V	05405-16V	05405-20V		
	FOR INTERLOCK FITTINGS								34.7	42.2	49.8		
									15 Internal 52 External	17 Internal 67 External	21.5 Internal 74 External		
R13	FERRULE											05406-24V	05406-32V
	FOR INTERLOCK FITTINGS											59.7	78.2
												22 Internal 81 External	29 Internal 85 External
R15	FERRULE								05405-12V	05405-16V			
	FOR INTERLOCK FITTINGS								33.9	41.5			
									15 Internal 52 External	17 Internal 67 External			
R15	FERRULE										05406-20V	05406-24V	05406-32V
	FOR INTERLOCK FITTINGS										53.3	61.3	77.4
											21.5 Internal 74 External	22 Internal 81 External	29 Internal 85 External
EVEREST 6000 4C	FERRULE								05405-12	05405-16	05405-20		
	FOR INTERLOCK FITTINGS								33.2	40.2	50.2		
									15 Internal 52 External	17 Internal 67 External	21.5 Internal 74 External		
EVEREST 6000 4C	FERRULE								05400-12	05400-16	05400-20		
	FOR STANDARD FITTINGS								36.2	43.4	53.4		
									n.s	n.s	n.s		
EVEREST 6000 4C	FERRULE								05404-12	05404-16	05404-20		
	FOR STANDARD FITTINGS								33.6	40.1	50.1		
									36	48	54		

(EVEREST 6000 4C) NOTE: 05400 & 05404 FERRULES ARE SUITABLE FOR APPLICATIONS REACHING A MAXIMUM OF 350 BAR

EHRCO Limited

Unit H
Peartree Business Park
Crackley Way
Peartree Lane
Dudley
DY2 0UW

sales@ehrco.ltd.uk

www.ehrco.co.uk

T: 01384 245 000